

WEATHERBOARDS - PRODUCT SPECIFICATION

BGC Stratum™

BGC STRATUM™

An alternative to traditional weatherboards, Stratum™ is a trio of plank products. Choose one Stratum™ profile as a standalone, or use a combination of the three different profiles available.

APPLICATION

Exterior cladding

AUSTRALIAN STANDARDS

Manufactured to conform to the requirements of AS2908.2 Cellulose-Cement Products and are classified as Type A Category 3 for external use.

Tested in accordance to AS1530.3

PROFILES

/ Stratum™ – 300mm wide plank with 16mm horizontal joint

/ Stratum™ Duo – 30mm wide plank with 16mm centre groove

/ Stratum™ Contour – 170mm wide plank with a 2mm indentation at the top of each plank

INSTALLATION

Ensure double 35mm studs are installed at all vertical flashing strip joints, refer to framing section in BGC Stratum™ brochure for alternative framing.

When using screws to fasten Stratum™, pre countersinking is suggested so that the fastener is 2mm under the plank surface for filling with epoxy filler and BGC Exterior Finishing Compounds.

BGC Stratum™ is designed to be installed horizontally to both timber and lightweight steel frames.

BGC Stratum™ can be installed both on stud and off stud. Refer to the BGC Stratum™ brochure for various joining methods.

BGC Stratum™ can be either face fixed or conceal fixed. Gun nailing is suitable only for face fixing and cannot be used for concealed fixing. Refer to the BGC Stratum™ brochure for installation methods.

Refer to the BGC Stratum™ brochure for complete installation instructions – www.bgcinnovadesign.com.au